



DIM2415

Digital Dimmerrack 24 x 3 kVA with power distributor PLA lighting 24 Channel Dimmer Rack comes equipped with two 12 x 3 kVA PLA lighting Digital Dimmer Units.

This rack is fitted with 460 A Powerlock distribution panel, RCD protection, a mains breaker, as well as 12 socapex (4 for dimmer 2x2 and 8 direct).

The rack is delivered completely wired and in full working order.

The dimmer units are protected with a 16A breaker on each phase.

The shockproof case offers optimal safety during transport.

The rack is delivered with two 12 x 3 kVA PLA Digital Dimmer units and 460 A Powerlock distribution connectors.

SPECIFICATIONS

Voltage	170V - 240V
---------	-------------

Frequency	45Hz-65Hz
-----------	-----------

Fade Accuracy	16bit
---------------	-------

Auto Voltage Compensation	Effective When Input At 10% Variation
---------------------------	---------------------------------------

Power Consumption	60W
-------------------	-----

Output	3KW For Each 24 Channels
--------	--------------------------

Signal	DMX512 (USITT 1990)
--------	---------------------

Dimming Range	0-100%
---------------	--------

Response Time	23ms
---------------	------

Pre-Heating	0-10%
-------------	-------

IP Rating	IP 33
-----------	-------

Output Connector Types	Socapex
------------------------	---------

Dimensions (H x W x D) mm	1130 x 580 x 810
---------------------------	------------------

Weight	130 Kg
--------	--------

